


1. TUBE TO BE SUPPLIED IN ACCORDANCE WITH CROSS SECTION SHOWN (DETAIL 'B').
2. TO BE SUPPLIED IN LENGTHS OF 42 METRES WOUND ON EDGE AS SHOWN AND SECURED WITH TAPE.
3. INDIVIDUAL COILS TO BE SEPARATED WITH BROWN PAPER.
4. FINISH - CLEAN.
5. PRESSURE TIGHT TO 300 PSI.

					MATERIAL: ALUMINIUM GRADE 1370 EC 99.7% (MIN) PURE. TEMPER AS EXTRUDED (SOFT)	PROTECTIVE FINISH: NONE	ALL DIMENSIONS IN mm FOR EXPLANATION OF DIMENSIONS, NOTES, SYMBOLS etc. SEE BS 8888  3rd ANGLE PROJECTION	WEIGHT (kg)	SCALE (ORIG)	TITLE ARMATURE TUBE, K125			
								8.16	1:5				
								GENERAL TOLERANCES (UNLESS OTHERWISE STATED)					
2	TUBE ROTATED 90°	CEEMA/AB	-	21/05/2021				BS EN 22768 CLASS m		DRAWING No. V500986	REV 2	SHEET 1 / 1	SIZE A2
1	INITIAL ISSUE	CEEMA/AB	-	12/02/2021				1g Dynamics 5 Dunsbridge Business Park, Shepreth, SG8 6RA, UK					
REV	DESCRIPTION	DRN	APPD	DATE									